

RETRACTABLE HANDLES WITH THREADED BUSHING
Colour: Black, Orange.
Material: tightening lever and clamping element: high resistance, fibreglass-reinforced technopolymer, solvent, fuel, grease and oil resistant.
Bushing: galvanised steel. (special inserts in brass and stainless steel on request)
Retaining spring and retaining screw material: burnished steel


Black Code	Dimensions (mm.)										Insert		weight gr.	Standard package from pc.
	A	B	D	S	H	H1	h1	h3	d1	h2	d	l		
MRB M5	40	48.3	18.6	8.5	39	42.5	31.5	13	12	7	M5	12	22	10 - 50 - 100
MRB M6	40	48.3	18.6	8.5	39	42.5	31.5	13	12	7	M6	12	22	10 - 50 - 100
MRB M6/2	55	65	22	9	49	53	37	14.5	15	10	M6	14	26	10 - 50 - 100
MRB M8	55	65	22	9	49	53	37	14.5	15	10	M8	14	26	10 - 50 - 100
MRB M8/2	80	93.5	29	11.5	68	72.5	48	18	20	12	M8	20	56	10 - 50 - 100
MRB M10	80	93.5	29	11.5	68	72.5	48	18	20	12	M10	20	55	10 - 50 - 100
MRB M12	80	93.5	29	11.5	68	72.5	48	18	20	12	M12	27	57	10 - 50 - 100
MRBM12/2	102	119	38	17	85	89.5	60	22	25	12	M12	27	113	10 - 50 - 100
MRB M14	102	119	38	17	85	89.5	60	22	25	12	M14	27	124	10 - 50 - 100
MRB M16	102	119	38	17	85	89.5	60	22	25	12	M16	27	119	10 - 50 - 100

Orange Code	Dimensions (mm.)										Insert		weight gr.	Standard package from pc.
	A	B	D	S	H	H1	h1	h3	d1	h2	d	l		
MAR M5	40	48.3	18.6	8.5	39	42.5	31.5	13	12	7	M5	12	22	10 - 50 - 100
MAR M6	40	48.3	18.6	8.5	39	42.5	31.5	13	12	7	M6	12	22	10 - 50 - 100
MAR M6/2	55	65	22	9	49	53	37	14.5	15	10	M6	14	26	10 - 50 - 100
MAR M8	55	65	22	9	49	53	37	14.5	15	10	M8	14	26	10 - 50 - 100
MAR M8/2	80	93.5	29	11.5	68	72.5	48	18	20	12	M8	20	56	10 - 50 - 100
MAR M10	80	93.5	29	11.5	68	72.5	48	18	20	12	M10	20	55	10 - 50 - 100
MAR M12	80	93.5	29	11.5	68	72.5	48	18	20	12	M12	27	57	10 - 50 - 100
MAR M12/2	102	119	38	17	85	89.5	60	22	25	12	M12	27	113	10 - 50 - 100
MAR M14	102	119	38	17	85	89.5	60	22	25	12	M14	27	124	10 - 50 - 100
MAR M16	102	119	38	17	85	89.5	60	22	25	12	M16	27	119	10 - 50 - 100

