


TAPERED SILICONE CAPS


Colour: Natural
Material: Silicone.
Resistant up to + 300° C.



Code	Dimensions (mm.)			Usage references			Standard package
	D	d	H	GAS	UNF	METRIC	
TSL04	1.6	0.4	15.9	-	-	-	1'000
TSL05	2	0.5	19.1	-	-	M2	1'000
TSL08	3.2	0.8	15.9	-	-	M2	1'000
TSL1.6	3.2	1.6	15.9	-	-	M3	1'000
TSL1.6/1	4.8	1.6	15.9	-	-	M3-M4	1'000
TSL1.6/2	4.8	1.6	19.1	-	-	M3-M4	1'000
TSL1.2	5.5	1.2	38.1	-	-	M3-M4-M5	1'000
TSL3.2	6.4	3.2	19.1	-	1/4"	M5-M6	1'000
TSL3.2/1	6.4	3.2	25.4	-	1/4"	M5-M6	1'000
TSL4.8	8.7	4.8	15.9	1/16"	5/8"	M7-M8	1'000
TSL4.8/1	8.7	4.8	25.4	1/16"	5/8"	M7-M8	1'000
TSL6.4	9.5	6.4	12.7	1/8"	3/8"	M10	100
TSL6.4/1	9.5	6.4	19.1	1/8"	3/8"	M10	100
TSL8.7	11.1	8.7	17.5	-	7/16"	M12	100
TSL6.4/2	11.1	6.4	25.4	1/8"	3/8"	M10-M12	500
TSL8.7/1	11.9	8.7	20.6	-	7/16"	M12	500
TSL7.9	14.3	7.9	28.6	1/4"	7/16"-1/2"-9/16"	M10-M12-M14	100
TSL7.9/1	14.3	7.9	25.4	1/4"	7/16"-1/2"-9/16"	M10-M12-M14	100
TSL10.3	15.1	10.3	25.4	-	1/2"-9/16"	M14-M16	100
TSL11.1	15.9	11.1	22.2	3/8"	9/16"-5/8"	M14-M16	100
TSL12.7	16.7	12.7	25.4	3/8"	5/8"	M16	200
TSL11.1/1	17.5	11.1	25.4	3/8"	5/8"	M14-M16-M18	100
TSL14.3	19.1	14.3	14.3	-	3/4"	M18-M20	100
TSL14.3/1	19.1	14.3	25.4	-	3/4"	M18-M20	100
TSL15.9	19.8	15.9	25.4	1/2"	3/4"	M20	100
TSL15.9/1	20.3	15.9	15.9	1/2"	3/4"	M20-M22	100

TAPERED SILICONE CAPS

Colour: Natural
Material: Silicone.
Resistant up to + 300° C.



Code	Dimensions (mm.)			Usage references			Standard package
	D	d	H	GAS	UNF	METRIC	
TSL19.1	23.5	19.1	19.1	-	7/8"	M22-M24	100
TSL18.3	23.8	18.3	25.4	-	7/8"	M22-M24	100
TSL19.8	25.4	19.8	25.4	3/4"	1"	M24-M27	100
TSL23	27	23	25.4	-	-	M27	100
TSL23.8	27.9	23.8	25.4	-	1.1/8"	M30	100
TSL26.2	31.8	26.2	25.4	-	1.1/4"	M33	100
TSL27	33.4	27	25.4	1"	1.1/4"-1.3/8"	M33	100
TSL30.2	36.5	30.2	25.4	-	1.3/8"	M36	100
TSL31.8	38.9	31.8	25.4	-	1.1/2"	M39	100
TSL33.3	41.3	33.3	25.4	1.1/4"	1.1/2"	M39-M42	100
TSL35.7	42.9	35.7	25.4	1.1/4"	-	M42	100
TSL37.3	44.5	37.3	25.4	-	-	M48	100
TSL38.1	46	38.1	25.4	1.1/2"	-	M48	100
TSL41.3	50	41.3	25.4	1.1/2"	-	-	50
TSL44.5	52.4	44.5	25.4	-	-	M56	50
TSL47.6	56	47.6	25.4	-	-	M56	50
TSL50	62.7	50	25.4	2"	-	M64	50
TSL54	63.5	54	25.4	2"	-	M64	50
TSL57.9	68.3	57.9	25.4	-	-	-	50
TSL61.9	75	61.9	34.9	2.1/2"	-	-	50
TSL76.2	88.9	76.2	38.1	3"	-	-	10
TSL82.6	101.6	82.6	38.1	-	-	-	10
TSL88.9	127	88.9	50.8	4"	-	-	5